



**NATURAL GAS VEHICLE COOPERATIVE PURCHASING PROGRAM**  
**CNG Conversion Specs for Vehicle Configuration No. 16:**  
**Chevrolet/GMC 2500 Pickup 4X2 – Extended Range – 8’ Bed**

<b>DEALER NAME</b> _____	<b>BID AMOUNT</b> _____	
		Mark "S" for standard, or specify deviations.
1) Make/Model	A) Heavy Duty Pickup, 8' Bed, <b><u>GMC or Chevrolet 2500</u></b> B) Show Make _____ Model _____	A. _____ B. _____
2) Rating	A) G.V.W.: 9,200 lbs, Show GVW _____ B) Payload: 2,500 lbs, Show Payload _____	A. _____ B. _____
3) Dimensions	A) Wheelbase: 133", Show Wheelbase _____ B) Pickup Box: 8 Foot Length	A. _____ B. _____
4) Engine	A) <b><u>Natural Gas Dedicated</u></b> : 6.0 Liter, V8 B) Show Engine C.I.D. or Liters _____	A. _____ B. _____
5) Cooling System	A) Maximum Capacity Cooling Available With Coolant Recovery System	A. _____
6) Air Cond.	A) Factory Installed With Integral Heater & Defroster	A. _____
7) Electrical	A) Battery: 12 Volt, 600 CCA B) Alternator: 12 Volt, 100 AMP C) Dual Note Electric Horns D) Roof Mounted Center High Mount Stop Light	A. _____ B. _____ C. _____ D. _____
8) Radio	A) AM/FM Stereo Radio With Manual Antenna	A. _____
9) Fuel System	A) CNG cylinder 21 GGE Minimum. 3600 psi. In The Bed Mounted And Shielded. Specify Capacity: _____ B) Extended Range 6 GGE Minimum. 3600 psi. Under Bed Mounted And Shielded. Specify Capacity: _____	A. _____ B. _____



- 10)Interior
  - A) Dome Light In Cab A. \_\_\_\_\_
  - B) 12 Volt Power Outlet Dash Mounted B. \_\_\_\_\_
  - C) Seat Belts: Lap and Shoulder C. \_\_\_\_\_
  - D) Gauges: Oil Pressure, Temperature, Ammeter, Speedometer  
And Natural Gas Pressure D. \_\_\_\_\_
  - E) Mirror: Inside Rear View, Day And Night E. \_\_\_\_\_
  - F) Sun Visors: Right And Left Side F. \_\_\_\_\_
  - G) Seat: 40-20-40 Split-Bench G. \_\_\_\_\_
  - H) Upholstery: Vinyl, Blue Color H. \_\_\_\_\_
  - I) Full Floor Mat: Black Rubber I. \_\_\_\_\_
  - J) Arm Rests: Right And Left Side Doors J. \_\_\_\_\_
  
- 11)Exterior
  - A) Cab: Conventional A. \_\_\_\_\_
  - B) Frame: Standard B. \_\_\_\_\_
  - C) Mirrors: Dual Manual, 6.5" x 9" Low Mount, Black,  
With Convex Right Side Mirror C. \_\_\_\_\_
  - D) Windows: Tinted Glass All Around D. \_\_\_\_\_
  - E) Wipers: Two Speed Intermittent With Washers E. \_\_\_\_\_
  
- 12)Axles
  - A) Front: 3,300 lbs Minimum, Show Capacity \_\_\_\_\_ A. \_\_\_\_\_
  - B) Rear: 4,800 lbs Minimum, Show Capacity \_\_\_\_\_ B. \_\_\_\_\_
  
- 13)Ratio
  - A) Show Standard Ratio For Powertrain \_\_\_\_\_ A. \_\_\_\_\_
  
- 14)Springs
  - A) Front: 3,300 lbs Minimum, Show Capacity \_\_\_\_\_ A. \_\_\_\_\_
  - B) Rear: 4,800 lbs Minimum, Show Capacity \_\_\_\_\_ B. \_\_\_\_\_
  - C) Stabilizer Bar: Front C. \_\_\_\_\_
  
- 15)Shocks
  - A) Heavy Duty Front And Rear A. \_\_\_\_\_
  
- 16)Brakes
  - A) Power Assist with Four-Wheel Anti-Lock A. \_\_\_\_\_
  - B) Front: Disc B. \_\_\_\_\_
  - C) Rear: Drum C. \_\_\_\_\_
  
- 17)Transmission
  - A) 6 Speed Automatic Overdrive With Auxiliary Transmission Oil Cooler A. \_\_\_\_\_
  - B) Column Mounted Transmission Shift Selector B. \_\_\_\_\_
  
- 18)Steering
  - A) Power A. \_\_\_\_\_
  
- 19)Tires
  - A) 5 Each: LT245/75R16-E, SBR-BSW, All-Season Tread A. \_\_\_\_\_
  
- 20)Wheels
  - A) 5 Each: 16.0 x 6.5 DC, To Match Tires A. \_\_\_\_\_
  - B) 5 Each: Trim Rings & Hub Caps B. \_\_\_\_\_



- |            |   |                      |
|------------|---|----------------------|
| 21)Spare   | A) Full Size Mounted Under Bed  | A. _____             |
| 22)Misc.   | A) All Emission Controls, Lights, And Safety Items To Be Furnished<br>And Operating In Compliance With California And Federal Laws. | A. _____             |
| 23)Paint   | A) Exterior: Bright White:  | A. _____             |
| 24)Bumpers | A) Front: Chrome<br>B) Rear Bumper: Installed by Body Builder   | A. _____<br>B. _____ |

**The Above Constitutes Our Basic Van, And Includes All The Above Equipment**

DEALER "MAKE READY" SHALL INCLUDE BUT SHALL NOT BE LIMITED TO THE FOLLOWING POINTS:

1. Exterior and Interior To Be Clean, Free Of Dust, Road Film, Preservatives, etc.
2. Paint Is To Fully Cover: No Thin Spots, No Noticeable Overspray, No Noticeable Runs.
3. Vehicle Is To Be Free Of Scratches And Body Damage.
4. Engine Timing Is To Be Per Factory Specifications. Noticeable Rough Running, Fast Idle Problems Are To Be Corrected.
5. Oil, Coolant, ATF, Brake Fluid Levels Are To Be Full.
6. Tire Pressure, (Including Spare. To Be Checked. Spare Tire Mounting Secure And Wheel Lug Nuts To Be Tight.
7. Steering Wheel To Be Centered.
8. All Lights, Signals, Horns And All Accessories Are To Be Operative.
9. All State and Federal Safety Regulations Are To Be Met.
10. Brakes Are To Be Checked For Proper Operation; No Spongy Pedal, No Pull.
11. Vehicle To Be Delivered With 3 Full Sets of Keys.

**IF THERE ARE ANY QUESTIONS REGARDING THE SPECIFICATIONS, PLEASE CONTACT DAVID KANTOR AT CALSTART AT 626-744-5611 OR [DKANTOR@CALSTART.ORG](mailto:DKANTOR@CALSTART.ORG).**